Rotary Vane Vacuum Pump

PASCAL Series

2100A or 2100 SD 85 CFM

Alcatel Adixen Pascal Series 2100A and 2100SD Rotary Vane Vacuum Pump Reputit



2100A or SD

Addresses the requirements of all major vacuum application for non-corrosive applications.







Specifications for 2100A or 2100SD


REBUILT A - SD PASCAL Series 2 Stages

Specifications		Un	its	2100A/SD
Part Number				P10975
Price (2009 Rebuilt Prices)			\$5,475
Nominal pumping speed (*	50H 60H		/h fm	120 85
Pneurop pumping speed (*	50H *) 60H		/h m	100 70.6
Ultimate partial pressure (*	*)	ml	oar	2.10 -4
Ultimate total pressure (*) closed gas ballast		ml	oar	3.10 -3
Ultimate total pressure (*) open gas ballast		ml	oar	3.10 -2
Water vapor capacity	50/60Hz	z g/	'n.	3000
Water vapor pressure	50/60H	lz mł	oar	40
Weight (max)		kg	(lbs)	231 (508)
Dimensions				ic to the rig
Electrical motors		20/380va 20/380va		0/415vac 0/480vac
Max nominal power rating	50/60Hz	z k'	N	3/3.6
Min ambient temperature		°C	(°F)	12 (54)
Max ambient temperature		°C ((°F)	45 (113)
Oil capacity			1	7.5
Inlet flange		ISO	-KF	DN 50
Exhaust flange		ISO	-KF	DN 50



Specific dimensions according to motors					
Motor type	L mm	D mm	H mm	a mm	b mm
VDE	310	196	140	44.5	86
CSA	305	195	140	44.5	86
JIS	310	196	140	44.5	86








Accessories for 2100A/SD Vacuum Pumps







Oil Mist eliminators retain oil mist contained in the exhausted gases with a high level of separation; an internal over pressure valve prevents exceeding the maximum exhaust pressure.

Heavy Duty Oil Mist Eliminator

Price\$80.85



2" Female NPT **inlet** requires **adapter** Male 2" to KF50 for use on Alcatel 2100SD outlet vacuum pumps

DE External Oil Filters For 2100A or SD

DE FILTERS retain solid particles and/or neutralizes corrosive products contained in the oil of the pump. DE filters can be connected to any rotary vane pump from 5 m³/h to 100 m³/h; all necessary components for connexion are included.

DE Filter Media DE1(1 Cartridge) DE2(2 Cartridges)

- Cellulose filter: filtration of solid particles only Applications: General Use
- Activated alumina: envelope/charge of activated alumina Applications: mineral acids. Lewis acids. Polar compounds.
- Activated charcoal: envelope/charge of activated charcoal.

Applications: Chlorinated products, water and chlorine, Nitrous vapors, Ammonia.





DE External Filters				
	DE1	DE2		
Price	\$5095.00	\$7260.00		
weight kg/lbs	12/24.6	17/37.4		
electrical supply	110/220V 50HZ	115/230V 60 HZ		
oil flow hydrocarbon synthetic	1000 - 1500 cm ³ /mn 1000 cm ³ /mn at 65° C			
P/N 110/115V	068991	104375		
220/230V	068990	104374		

Replacement Cartridges

Price	\$97.65	\$91.50	\$115.05
type	activated alumina	activated charcoal	cellulose
P/N	068880	068881	078212

□ standard (factory installed) cartridges are:

DE 1 : activated alumina

DE 2 : cellulose and activated alumina

□ oil volume : DE 1: 1.2 lit. - DE 2: 1.8 lit.